

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : AlphaPlus® 1-Butene

Material : 1036988, 1015419, 1037080, 1037081

Company : Chevron Phillips Chemical Company LP

Normal Alpha Olefins (NAO) 10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887 Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Emergency Overview

Danger

Form: Compressed gas **Physical state**: Gaseous **Color**: Colorless OSHA Hazards : Flammable Gas, Compressed Gas

Classification

: Flammable gases , Category 1

Gases under pressure, Compressed gas

Labeling

MSDS Number:100000068452 1/12

Version 2.0 Revision Date 2015-04-20

Symbol(s)





Signal Word : Danger

Hazard Statements : H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Precautionary Statements : Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces.

- No smoking. **Response:**

P377 Leaking gas fire: Do not extinguish, unless leak can be

stopped safely.

P381 Eliminate all ignition sources if safe to do so.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcinogen

by ACGIH.

SECTION 3: Composition/information on ingredients

Synonyms : Ethylethylene

1-Butylene Alpha-butene Butene-1 (C4) Alpha-Butylene

C4H8

Molecular formula : C4H8

Component	CAS-No.	Weight %
1-Butene	106-98-9	95 - 99
n-Butane	106-97-8	0 - 1

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Do not leave the victim

unattended.

MSDS Number:100000068452 2/12

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

If inhaled : If unconscious place in recovery position and seek medical

advice. If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious

person. If symptoms persist, call a physician.

SECTION 5: Firefighting measures

Flash point : $-80 \, ^{\circ}\text{C} \, (-112 \, ^{\circ}\text{F})$

Autoignition temperature : 383.89 °C (723.00 °F)

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Special protective equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : For safety reasons in case of fire, cans should be stored

separately in closed containments. Use a water spray to cool

fully closed containers.

Fire and explosion

protection

: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can

accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

SECTION 7: Handling and storage

Handling

MSDS Number:100000068452 3/12

Version 2.0 Revision Date 2015-04-20

Advice on safe handling

For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers

Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

us

Ingredients	Basis	Value	Control parameters	Note
1-Butene	ACGIH	TWA	250 ppm,	
n-Butane	OSHA Z-1-A	TWA	800 ppm, 1,900 mg/m3	
	VCCIH	CTEI	1.000 ppm	*

^{* 2013} Adoption

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

MSDS Number:100000068452 4/12

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic

footwear.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : Compressed gas

Physical state : Gaseous Color : Colorless

Safety data

Flash point : -80 °C (-112 °F)

Lower explosion limit : 1.6 %(V)

Upper explosion limit : 9.3 %(V)

Oxidizing properties : no

Autoignition temperature : 383.89 °C (723.00 °F)

Molecular formula : C4H8

Molecular weight : 56.12 g/mol

pH : Not applicable

Freezing point : -185 °C (-301 °F)

pour point No data available

Boiling point/boiling range : -6.26 °C (20.73 °F)

Vapor pressure : 1,895.00 MMHG

at 20 °C (68 °F)

Relative density : 0.6

at 15.6 °C (60.1 °F)

MSDS Number:100000068452 5/12

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

Density : 600.3 g/l

Water solubility : Soluble in hydrocarbon solvents; insoluble in water.

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : No data available

Relative vapor density : 1.93

(Air = 1.0)

Evaporation rate : No data available

Percent volatile : > 99 %

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, sparks, fire, and oxidizing agents.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Hazardous decomposition

products

: Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Acute oral toxicity

1-Butene :

not applicable

Acute inhalation toxicity

n-Butane : LC50: 658 mg/l

Exposure time: 4 h

Species: rat

Test atmosphere: vapor

Acute dermal toxicity

1-Butene :

No data available

Skin irritation

MSDS Number:100000068452 6/12

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

1-Butene : No skin irritation

Rapid evaporation of the liquid may cause frostbite.

Eye irritation

1-Butene : No eye irritation

Sensitization

1-Butene : No data available.

Repeated dose toxicity

1-Butene : Species: rat, Male and female

Sex: Male and female

Application Route: Inhalation Dose: 0, 500, 2000, 8000 ppm

Exposure time: 28 d

Number of exposures: 6 hr/d, 7 d/wk

NOEL: 8000 ppm

Method: OECD Guideline 422

No adverse effect has been observed in chronic toxicity tests.

n-Butane Species: rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 1017, 4489 ppm Exposure time: 90 day

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 4489 ppm

Carcinogenicity

1-Butene : Species: rat

Sex: male

Dose: 0, 500, 2000, 8000 ppm

Exposure time: 2 years

Number of exposures: 6 hr/d, 5 d/wk

Remarks: increased incidence of thyroid tumors, Information given is based on data obtained from similar substances.

MSDS Number:100000068452

7/12

Version 2.0 Revision Date 2015-04-20

Species: rat Sex: female

Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years

Number of exposures: 6 hr/d, 5 d/wk

Remarks: no increase incidence of tumors, Information given

is based on data obtained from similar substances.

Species: mouse Sex: male

Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years

Number of exposures: 6 hr/d, 5 d/wk

Remarks: no increase incidence of tumors, Information given

is based on data obtained from similar substances.

Species: mouse Sex: female

Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years

Number of exposures: 6 hr/d, 5 d/wk

Remarks: no increase incidence of tumors, Information given

is based on data obtained from similar substances.

Reproductive toxicity

1-Butene : Species: rat

Sex: male and female Application Route: Inhalation Dose: 0, 500, 2000, 8000 ppm Method: OECD Guideline 422 NOAEL Parent: 8000 ppm NOAEL F1: 8000 ppm

CMR effects

1-Butene : Carcinogenicity: Not classifiable as a human carcinogen.

Mutagenicity: Tests on bacterial or mammalian cell cultures

did not show mutagenic effects.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

AlphaPlus® 1-Butene

Further information : No data available.

SECTION 12: Ecological information

Elimination information (persistence and degradability)

Biodegradability : This material is expected to be readily biodegradable.

Results of PBT assessment

1-Butene : Non-classified PBT substance, Non-classified vPvB substance

MSDS Number:100000068452 8/12

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate

ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1012, BUTYLENE, 2.1 NON- ODORIZED

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1012, BUTYLENE, 2.1, (-80 °C) NON- ODORIZED

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1012, BUTYLENE, 2.1 NON- ODORIZED

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1012, 1-BUTYLENE, 2.1, (B/D) NON- ODORIZED

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1012, 1-BUTYLENE, 2.1 NON- ODORIZED

MSDS Number:100000068452 9/12

AlphaPlus® 1-Butene

Version 2.0 Revision Date 2015-04-20

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1012, 1-BUTYLENE, 2.1 NON- ODORIZED

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

National legislation

SARA 311/312 Hazards : Fire Hazard

Sudden Release of Pressure Hazard

EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO - KNOW

CERCLA Reportable

Quantity

: Calculated RQ exceeds reasonably attainable upper limit.

1,3-Butadiene

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

SARA 313 Ingredients : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

MSDS Number:100000068452 10/12

Version 2.0 Revision Date 2015-04-20

The following chemical(s) are listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F):

: n-Butane - 106-97-8

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know

: 1-Butene - 106-98-9 n-Butane - 106-97-8

New Jersey Right To Know

: 1-Butene - 106-98-9 n-Butane - 106-97-8

California Prop. 65

Ingredients

: WARNING! This product contains a chemical known in the

State of California to cause cancer.

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive

harm.


Notification status

Europe REACH On the inventory, or in compliance with the inventory United States of America TSCA On the inventory, or in compliance with the inventory Canada DSL On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory Australia AICS New Zealand NZIoC On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory Japan ENCS Korea KECI On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory Philippines PICCS On the inventory, or in compliance with the inventory China IECSC

SECTION 16: Other information

NFPA Classification : Health Hazard: 1

Fire Hazard: 4 Reactivity Hazard: 0



MSDS Number:100000068452 11/12

Version 2.0 Revision Date 2015-04-20

Further information

Legacy SDS Number : PE0015

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet					
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level		
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency		
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health		
CNS	Central Nervous System	NTP	National Toxicology Program		
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals		
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level		
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration		
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration		
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit		
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances		
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act		
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit		
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.		
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value		
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials		
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System		
LC50	Lethal Concentration 50%				

MSDS Number:100000068452 12/12