## MATERIAL SAFETY DATA SHEET

|-----|
| SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION |

PRODUCT NAME : PROTECTO-CRETE 350SD COMP. B

IDENTIFICATION NUMBER: PCR350SDB00B PREPARE / REVISED: 08/07/06

PRODUCT USE/CLASS : EPOXY HARDENER

SUPPLIER: MANUFACTURER: Dudick, Inc. Dudick, Inc.

1818 Miller Parkway
Streetsboro, Ohio 44241
Streetsboro, Ohio 44241

CHEM-TEL: 800-255-3924 CHEM-TEL: 800-255-3924

24 HOURS A DAY 24 HOURS A DAY

PREPARER: DUDICK, INC., PHONE: 800-322-1970

=====	SECTION 2 - COMPOSITION/INFORMATION	ON INGREDIENTS	:======    
ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	ISOPHORONE DIAMINE	2855-13-2	25.0 %
02	BENZYL ALCOHOL	100-51-6	25.0 %
03	POLYPROPYLENEDIAMINE	9046-10-0	25.0 %
04	AMINE-EPOXY RESIN ADDUCT	UNKNOWN	20.0 %
05	PHENOLIC COMPOUND	UNKNOWN	20.0 %
06	TERTIARY AMINE	NO INFO	5.0 %

			EXPOSURE LIMIT	rs		
	A	CGIH	OSI	ΑŁ	COMPANY	
ITEM	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	NE	NE	NE	NE	NE	YES
02	NO INFO	NO INFO	NO INFO	NO INFO	NE	NO
03	NO INFO	NO INFO	NO INFO	NO INFO	NE	NO
04	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
05	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
06	NE	NE	NE	NE	NE	YES

(See Section 16 for abbreviation legend)

	ı
SECTION 3 - HAZARDS IDENTIFICATION	ĺ
======================================	ĺ

\*\*\* EMERGENCY OVERVIEW \*\*\*: DANGER!---CAUSES BURNS. HARMFUL IF SWALLOWED. DO NOT GET IN EYES, ON SKIN, OR CLOTHING. DO NOT BREATH VAPORS OR MISTS.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: EYE CONTACT MAY CAUSE SEVERE

(Continued on Page 2)

Product: PCR350SDB00B PREPARE / REVISED: 08/07/06 Page 2 |------SECTION 3 - HAZARDS IDENTIFICATION \_\_\_\_\_\_

IRRITATION WITH CORNEAL INJURY. MAY CAUSE BLINDNESS.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION AND BURNS. SEVERE SKIN IRRITANT.

EFFECTS OF OVEREXPOSURE - INHALATION: MAY CAUSE IRRITATION OF THE NOSE, THROAT, AND LUNGS. VAPORS AND MISTS MAY BE CORROSIVE TO THE RESPIRATORY TRACT.

EFFECTS OF OVEREXPOSURE - INGESTION: INGESTION MAY CAUSE BURNS TO THE MOUTH, THROAT, AND ESOPHAGUS. INGESTION MAY CAUSE NAUSEA, CRAMPS, VOMITING, AND DIARRHEA.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: ALLERGIC REACTIONS MAY OCCUR IN SOME INDIVIDUALS. PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT. MAY CAUSE SKIN SENSITIZATION.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

I	
ĺ	SECTION 4 - FIRST AID MEASURES
I	

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SUPPLEMENTAL OXYGEN MAY BE INDICATED. CALL A PHYSICIAN.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GIVE VICTIM PLENTY OF WATER TO DRINK IF CONSCIOUS.

ĺ	SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 226 F LOWER EXPLOSIVE LIMIT: N.A. (SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: MAY PRODUCE TOXIC CARBON MONOXIDE AND NITROGEN OXIDES UPON COMBUSTION.

SPECIAL FIREFIGHTING PROCEDURES: EVACUATE AREA. WATER MAY BE INEFFECTIVE BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE

(Continued on Page 3) \_\_\_\_\_\_ Product: PCR350SDB00B PREPARE / REVISED: 08/07/06 Page 3

SECTION 5 - FIRE FIGHTING MEASURES	

DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

|-----|
| SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA TO CONTAIN SPILLAGE. ABSORB EXCESS WITH SAND, EARTH, OR VERMICULITE. SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS.

|-----|
| SECTION 7 - HANDLING AND STORAGE |

HANDLING: IF BODILY CONTACT OCCURS, REMOVE CONTAMINATED CLOTHING AT ONCE. AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING VAPORS. FOR INDUSTRIAL USE ONLY. WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

STORAGE: DO NOT STORE NEAR INCOMPATIBLES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR WHEN EXPOSURE TO MISTS OR VAPORS IS LIKELY.

SKIN PROTECTION: IMPERVIOUS RUBBER OR NEOPRENE TYPE. CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED AS MINIMUM PROTECTION. GOGGLES RECOMMENDED FOR INDIVIDUALS MIXING THE RESIN AND CATALYST.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

|-----|
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |

BOILING RANGE : 401 - 500 F VAPOR DENSITY : Is heavier than air ODOR : AMMONIACAL ODOR THRESHOLD : NE

(Continued on Page 4)

Product: PCR350SDB00B PREPARE / REVISED: 08/07/06 Page 4

Ì	SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

EVAPORATION RATE: Is slower than Ether APPEARANCE : AMBER LIQUID

SOLUBILITY IN H2O : SLIGHT

FREEZE POINT : NE VAPOR PRESSURE : NE SPECIFIC GRAVITY: 1.03 PHYSICAL STATE : LIQUID VISCOSITY . ....

COEFFICIENT OF WATER/OIL DISTRIBUTION: NE

(See Section 16 for abbreviation legend)

|-----SECTION 10 - STABILITY AND REACTIVITY |-----|

CONDITIONS TO AVOID: HEAT, FLAME, CONTAMINANTS.

INCOMPATIBILITY: STRONG OXIDANTS. STRONG ACIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF NITROGEN. OXIDES OF CARBON. OTHER TOXIC ORGANIC SUBSTANCES MAY BE FORMED. AMMONIA WHEN HEATED.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

|-----SECTION 11 - TOXICOLOGICAL PROPERTIES |-----|

No product or component toxicological information is available.

|-----SECTION 12 - ECOLOGICAL INFORMATION |-----

ECOLOGICAL INFORMATION: DO NOT CONTAMINATE PONDS, STREAMS, OR UNDERGROUND WATER SUPPLY. ISOPHORONEDIAMINE IS BIODEGRADABLE.

|-----| SECTION 13 - DISPOSAL CONSIDERATIONS |-----|

DISPOSAL METHOD: FOLLOW ALL RELEVANT LOCAL, STATE, AND FEDERAL REGULATIONS. EMPTY DRUMS MAY CONTAIN RESIDUE OR FUMES WHICH ARE HARMFUL.

|-----SECTION 14 - TRANSPORTATION INFORMATION |-----|

DOT PROPER SHIPPING NAME: CORROSIVE LIQUID N.O.S.

DOT TECHNICAL NAME: POLYAMINES

DOT HAZARD CLASS: 8 HAZARD SUBCLASS: NA

DOT UN/NA NUMBER: UN1760 PACKING GROUP: II RESP. GUIDE PAGE: 154

(Continued on Page 5)

\_\_\_\_\_\_

(Continued on Page 6)

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER
No non-hazardous ingredients are present at greater than 3%.

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: E

|-----|
| SECTION 16 - OTHER INFORMATION |

HMIS RATINGS - HEALTH: 3\* FLAMMABILITY: 1 REACTIVITY: 0

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.00 lbs/gal, 0 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

\_\_\_\_\_\_

The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.

\_\_\_\_\_\_

<END OF MSDS>