

HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: DCA-19003

Revision Date: 16-Jun-2014

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DCA-19003

Synonyms: None

Chemical Family: Blend

Application: Crosslinker

Manufacturer/Supplier Halliburton Energy Services, Inc.

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Propanol	71-23-8	10 - 30%	TWA: 100 ppm	200 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause severe eye irritation. May be harmful if swallowed. May cause headache, dizziness, and other central nervous system effects. May cause lung damage if swallowed. May be absorbed through the skin. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Activated charcoal or gastric lavage may be advisable for significant ingestion.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	84
Flash Point/Range (C):	28
Flash Point Method:	PMCC
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined
Fire Extinguishing Media	Water fog, carbon dioxide, foam, dry chemical.
Special Exposure Hazards	May be ignited by heat, sparks or flames. Fight fire from a safe distance and from a protected location. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.
Special Protective Equipment for Fire-Fighters	Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.
NFPA Ratings:	Health 2, Flammability 3, Reactivity 0
HMIS Ratings:	Health 2, Flammability 3, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures	Use appropriate protective equipment.
Environmental Precautionary Measures	Prevent from entering sewers, waterways, or low areas.
Procedure for Cleaning / Absorption	Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions	Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another.
Storage Information	Store away from oxidizers. Store away from acids. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 12 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls	Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.
Respiratory Protection	Organic vapor respirator.
Hand Protection	Impervious rubber gloves.
Skin Protection	Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Yellow
Odor:	Alcohol
pH:	7-9
Specific Gravity @ 20 C (Water=1):	1.091
Density @ 20 C (lbs./gallon):	9.09
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	210
Boiling Point/Range (C):	98
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid Keep away from heat, sparks and flame.

Incompatibility (Materials to Avoid) Strong oxidizers. Strong acids.

Hazardous Decomposition Products Olefins. Oxides of nitrogen. Other organic materials. Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure

Acute Toxicity

Inhalation

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact

May cause severe eye irritation.

Skin Contact

May cause skin irritation. May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion. May cause an allergic skin reaction.

Ingestion	Aspiration can be a hazard if this material is swallowed. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions.
Chronic Effects/Carcinogenicity	No data available to indicate product or components present at greater than 1% are chronic health hazards.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Propanol	71-23-8	5400 mg/kg (Rat) 6500 mg/kg (Rat) 8000 mg/kg (Rat) 1870 mg/kg (Rat)	4032 mg/kg (Rabbit) 4055 mg/kg (Rabbit)	13548 ppm (Rat) 4 h

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Propanol	71-23-8	EC50(48h): 9170 mg/L (Pseudokirchnerella subcapitata)	LC50(96h): 4555 mg/L (Pimephales promelas)	IC50(3h): > 1000 mg/L (activated sludge, domestic)	EC50(48h): 1000 mg/L (Gammarus pulex) EC50(48h): 3644 mg/L (Daphnia magna) NOEC(21d): > 100 mg/L (Daphnia magna)

12.2 Persistence and degradability

No information available

Substances	Persistence and Degradability
Propanol	Readily biodegradable (76% @ 10d)

12.3 Bioaccumulative potential

No information available

Substances	Log Pow
Propanol	0.2

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

US DOT

UN Number: UN1274
UN Proper Shipping Name: n-Propanol Solution
Transport Hazard Class(es): 3
Packing Group: III
NAERG: NAERG 129

US DOT Bulk

DOT (Bulk) Not Applicable

Canadian TDG u10

UN Number: UN1274
UN Proper Shipping Name: n-Propanol Solution
Transport Hazard Class(es): 3
Packing Group: III

IMDG/IMO

UN Number: UN1274
UN Proper Shipping Name: n-Propanol Solution
Transport Hazard Class(es): 3
Packing Group: III
EMS: EmS F-E, S-D

IATA/ICAO

UN Number: UN1274
UN Proper Shipping Name: n-Propanol Solution
Transport Hazard Class(es): 3
Packing Group: III

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Special Precautions for User None

Labels:

Flammable Liquid

15. REGULATORY INFORMATION**US Regulations**

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA (313) Chemicals This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity Not applicable.

EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of: Ignitability D001
California Proposition 65	All components listed do not apply to the California Proposition 65 Regulation.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	Product contains one or more components not listed on the inventory.
WHMIS Hazard Class	B2 Flammable Liquids D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS
Not applicable

Additional information	For additional information on the use of this product, contact your local Halliburton representative. For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.
Disclaimer Statement	This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****