

# **Material Safety Data Sheet**

Issuing Date 29-Apr-2011 Revision Date Revision Number 0

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name EP200W16 MO WATERBORNE PAINT

Product Code(s) 982521

Recommended Use Traffic paint

Product Technology W/B

Supplier Address

Ennis Paint Inc.
5910 North Central Expressway

Suite 1050 Dallas TX 75206 T: 800.331.8118

800.331.8118 (For Technical Inquiries)

Chemical Emergency Phone Number Chemtrec 1-800-424-9300

#### 2. HAZARDS IDENTIFICATION

#### DANGER!

### **Emergency Overview**

Harmful by inhalation, in contact with skin and if swallowed Causes central nervous system depression.

May cause skin, eye, and respiratory tract irritation May adversely affect liver and kidney.

Cancer hazard

WARNING! This product contains a chemical known in the State of California to cause cancer.

Appearance White Physical State Emulsion. Odor Slight, Ammonia

**Potential Health Effects** 

Ingestion

**Principle Routes of Exposure** Eye contact. Skin contact. Inhalation.

**Acute Toxicity** 

**Eyes** May cause irritation.

**Skin** Harmful if absorbed through skin. May cause irritation.

**Inhalation** Harmful by inhalation. May cause central nervous system depression with nausea, headache,

dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled. Harmful if swallowed. May cause blindness if swallowed. May cause additional affects as listed

under "Inhalation".

Chronic Effects Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment

and lung damage. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. Inhalation, ingestion, or skin absorption of

methanol can cause blindness.

**Aggravated Medical Conditions** Respiratory disorders. Lungs. Pre-existing eye disorders. Skin disorders. Liver disorders.

Kidney disorders. Central nervous system.

**Interactions with Other Chemicals** Use of alcoholic beverages may enhance toxic effects.

**Environmental Hazard**Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 12 for additional Ecological Information.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Titanium dioxide	13463-67-7	7-13
Methyl alcohol	67-56-1	1-5
Quartz	14808-60-7	1-5
Propylene glycol	57-55-6	1-5

# 4. FIRST AID MEASURES

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

symptoms persist, call a physician.

**Skin Contact**Wash off immediately with plenty of water. Remove and wash contaminated clothing before re-

use. If symptoms persist, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink

plenty of water. If symptoms persist, call a physician.

Notes to Physician Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable.

**Flash Point** > 201°F / 93.8°C

environment.

**Explosion Data** 

Sensitivity to Mechanical Impact None Sensitivity to Static Discharge None

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

NFPA Health Hazard 1 Flammability 1 Instability 0 Physical and Chemical

Hazards -

HMIS Health Hazard 2\* Flammability 1 Physical Hazard 0 Personal Protection -

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Avoid contact with skin, eyes

and clothing.

**Environmental Precautions** Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Use personal protective equipment. Dike far ahead of liquid spill for later disposal. Soak up

with inert absorbent material. Clean up promptly by sweeping or vacuum. Keep in suitable and

closed containers for disposal.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid contact with skin, eyes

and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or

smoke when using this product.

Storage Keep container tightly closed. Keep in properly labeled containers. Keep out of the reach of

children.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7		(vacated) TWA: 10 mg/m³total dust	_
Quartz	TWA: 0.025 mg/m³respirable fraction	TWA: 0.1 mg/m³ (vacated)	IDLH: 50 mg/m³ respirable dust
14808-60-7			TWA: 0.05 mg/m³ respirable dust
Methyl alcohol	STEL = 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 260 mg/m <sup>3</sup>
		(vacated) TWA: 260 mg/m <sup>3</sup>	STEL: 325 mg/m <sup>3</sup>
		(vacated) STEL: 250 ppm	STEL: 250 ppm
		(vacated) STEL: 325 mg/m <sup>3</sup>	
		(vacated) S*	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Engineering Measures Showers

Eyewash stations Ventilation systems

**Personal Protective Equipment** 

Eye/Face Protection Skin and Body Protection Respiratory Protection Wear protective eyewear (safety glasses).

Protective gloves.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance

with current local regulations.

**Hygiene Measures** Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes

and clothing. Wash hands before breaks and immediately after handling the product. Keep

away from food, drink and animal feeding stuffs.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceWhite.OdorSlight, Ammonia.

Odor Threshold No information available Physical State Emulsion

**pH** No information available.

Flash Point > 201°F / 93.8°C Autoignition Temperature No information available.

Decomposition Temperature No information available.

Boiling Point/Boiling Range No information available

Melting Point/Range No information available

Flammability Limits in Air No information available. Explosion Limits No information available.

Specific Gravity 1.55 - 1.75 Solubility Insoluble

Evaporation Rate No information available Vapor Pressure No data available

Vapor Density No data available EPA VOC (g/l) <100

### 10. STABILITY AND REACTIVITY

**Stability** Stable under recommended storage conditions.

Incompatible Products

None known based on information supplied.

Conditions to Avoid None known based on information supplied.

Hazardous Decomposition Products Carbon oxides. Nitrogen oxides (NOx).

**Hazardous Polymerization** Hazardous polymerization does not occur.

# 11. TOXICOLOGICAL INFORMATION

### **Acute Toxicity**

**Product Information** 

No acute toxicity information is available for this product.

#### **Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Titanium dioxide	> 10000 mg/kg (Rat)		> 6820 mg/m <sup>3</sup>
Quartz	500 mg/kg (Rat)		
Propylene glycol	20000 mg/kg (Rat)	= 20800 mg/kg ( Rabbit )	-
Methyl alcohol	5628 mg/kg (Rat)	15800 mg/kg ( Rabbit )	83.2 mg/L (Rat)4 h
			64000 ppm (Rat) 4 h

#### **Chronic Toxicity**

**Chronic Toxicity** 

Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment and lung damage. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. Inhalation, ingestion, or skin absorption of methanol can cause blindness.

#### Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
Quartz	A2	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

**OSHA: (Occupational Safety & Health Administration)** 

X - Present

**Target Organ Effects** 

Respiratory system. Central nervous system (CNS). Eyes. Skin. Liver. Kidney.

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol	-	LC50 96 h: 13500 - 17600	EC50 = 39000 mg/L 25 min	-
-		mg/L flow-through (Lepomis	EC50 = 40000 mg/L 15 min	
		macrochirus)	EC50 = 43000 mg/L 5 min	
		LC50 96 h: 18 - 20 mL/L		
		static (Oncorhynchus mykiss)		
		LC50 96 h: 19500 - 20700		
		mg/L flow-through		
		(Oncorhynchus mykiss)		
		LC50 96 h: = 28200 mg/L		
		flow-through (Pimephales		
		promelas)		
		LC50 96 h: > 100 mg/L static		
		(Pimephales promelas)		
Propylene glycol	EC50 96 h: = 19000 mg/L	LC50 96 h: 41 - 47 mL/L	EC50 = 710 mg/L 30 min	EC50 48 h: > 1000 mg/L
	(Pseudokirchneriella	static (Oncorhynchus mykiss)		Static (Daphnia magna)
	subcapitata)	LC50 96 h: = 51400 mg/L		EC50 24 h: > 10000 mg/L
		static (Pimephales promelas)		(Daphnia magna)
		LC50 96 h: = 51600 mg/L		
		static (Oncorhynchus mykiss)		
		LC50 96 h: = 710 mg/L		
		(Pimephales promelas)		

Chemical Name	Log Pow
Methyl alcohol	-0.77

### 13. DISPOSAL CONSIDERATIONS

#### **Waste Disposal Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

### **Contaminated Packaging**

Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol - 67-56-1		Included in waste stream:		U154
		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl alcohol	Toxic
·	Ignitable

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

# 15. REGULATORY INFORMATION

#### **International Inventories**

TSCA All components are listed on the TSCA Inventory.

DSL All components are listed either on the DSL or NDSL.

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	1-5	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

### **U.S. State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Propylene glycol	X	-	X	-	Х
Titanium dioxide	X	X	X	-	X
Quartz	X	X	X	-	X
Methyl alcohol	X	X	X	X	X

### **International Regulations**

Chemical Name	Carcinogen Status	Exposure Limits
Methyl alcohol		Mexico: TWA= 200 ppm
		Mexico: TWA= 260 mg/m <sup>3</sup>
		Mexico: STEL= 250 ppm
		Mexico: STEL= 310 mg/m <sup>3</sup>
Titanium dioxide		Mexico: TWA= 10 mg/m <sup>3</sup>
		Mexico: STEL= 20 mg/m <sup>3</sup>
Quartz		Mexico: TWA= 0.1 mg/m <sup>3</sup>

### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

D1B Toxic materials D2A Very toxic materials D2B Toxic materials



Chemical Name	NPRI
Methyl alcohol	X

# **16. OTHER INFORMATION**

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501 29-Apr-2011

Issuing Date Revision Date

29-Api-2011

Revision Note Initial Release.

#### **General Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

**End of Safety Data Sheet**