# MATERIAL SAFETY DATA SHEET

# **MULAY BLEND**

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Tarr Acquisition, LLC

4115 W. Turney Avenue

Phoenix, AZ 85019

**INFORMATION PHONE:** (602) 233-2000

EMERGENCY PHONE: CHEMTREC 800-424-9300 (US) Day or night

International Call Collect CHEMTREC 202-483-7616

PRODUCT NAME: MULAY BLEND

**PRODUCT NUMBER:** 3009

**UPC NUMBER:** 

PREPARED BY: Patricia Rodabaugh

 DATE PREPARED:
 11/16/2004

 LAST REVISION:
 3/12/1998

 SYNONYMS:
 MB

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS # W	eight %	OSHA PEL	ACGIH TLV	NOTE
2-Propanol	67-63-0	23-27	400 ppm	400 ppm	
Acetone	67-64-1	23-27	750 ppm	750 ppm	
Methyl isobutyl ketone	108-10-1	3-7	50 ppm	50 ppm	
2-Butoxyethanol	111-76-2	8-12	25 ppm (skin)	25 ppm (skin)	
Propylene glycol monomethyl ether	107-98-2	8-12	N/A	100 ppm	

## 3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING! Flammable liquid and vapor. Vapor harmful.

## POTENTIAL HEALTH EFFECTS

**EYE CONTACT:** Moderately irritating to the eyes.

**INHALATION:** May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS)

depression.

INGESTION: Irritating to the gastrointestinal tract, causing abdominal pain and vomiting, sometimes bloody. Ingestion may casue

CNS depression, low blood pressure, rapid heart beat and liver damage.

**SKIN CONTACT:** Mildly irritating to the skin.

# SIGNS AND SYMPTOMS OF EXPOSURE:

Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea: In extreme cases, unconsciousness and death may occur. Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

# 4. FIRST AID MEASURES

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation

persists, get medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be

3009 Page 1 of 4



Portland, Oregon Phoenix, Arizona Auburn, Washington Vancouver, Washington

**Print Date:** 11/16/2004

administered by qualified personnel. Get medical attention immediately.

**INGESTION:** Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce

vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's

head below hips while vomiting. Call doctor.

**SKIN CONTACT:** Flush skin with water. If irritation occurs, get medical attention.

## **AGGRAVATED MEDICAL CONDITIONS:**

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impared function from preexsiting disorders may be aggravated by exposure to this product.

#### SUPPLEMENTAL HEALTH INFORMATION:

See last page of MSDS for Supplemental Health Information.

## 5. FIRE FIGHTING MEASURES

## FLAMMABLE PROPERTIES

FLASH POINT: 70 F FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: NDA LEL: 0.0 UEL: 0.138

## **EXTINGUISHING MEDIA:**

Use water fog, "alcohol" foam, dry chemical, or CO2.

#### SPECIAL FIRE FIGHTING PROCEDURES:

WARNING. Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

## UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

## **COMBUSTION PRODUCTS:**

Carbon monoxide and unidentified organic compounds may be formed during combustion.

## 6. ACCIDENTAL RELEASE MEASURES

# STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

## 7. HANLDING AND STORAGE

# PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

## **OTHER PRECAUTIONS:**

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

## RESPIRATORY PROTECTION:

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-suppling respir. of an air-purifying respir. for organic vapors.

3009 Page 2 of 4

#### **VENTILATION:**

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

## **PROTECTIVE GLOVES:**

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

## EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

## **WORK / HYGENIC PRACTICES:**

Use good personal hygiene when handling this product. Wash hands after use, before smoking, or using the toilet.

#### **ENGINEERING CONTROLS:**

Facilities storing or utilizing this material should be equipped with and eyewash facility and a safety shower.

## **EXPOSURE GUIDELINES:**

Avoid prolonged or repeated breathing of vapors

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**SOLUBILITY IN WATER:** Infinite in water

**APPEARANCE AND ODOR:** Colorless, clear liquid. Mild odor.

**BOILING POINT:** 133 F **PERCENT VOLATILE:** 100

VAPOR PRESSURE: 8 - 180 mmHg @ 20 C PH:

EVAPORATION RATE: Slower than ether MOLECULAR WEIGHT:

POUNDS PER GALLON: VAPOR DENSITY: Heavier than air

SPECIFIC GRAVITY: 60.38 OTHER PROPERTIES:

MELTING POINT: NDA FREEZING POINT: NDA

# 10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum

equipment at temperatures above 120 deg. F.

## INCOMPATIBILITY:

Strong oxidizers.

#### HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition. Do not store or handle in aluminum equipment at temperatures ab

## 11. TOXICOLOGY INFORMATION

Exposure of rats by inhalation to 2-butoxyethanol caused hemolysis, hemoglobinuria (blood in the urine) and a slight increase in liver weight.

3009 Page 3 of 4

Other species, including man, were much less sensitive to hemolysis. The hemolytic effect seen in rats was transitory and/or reversible and not considered to be relevant to human health.

## 12. ECOLOGICAL INFORMATION

Keep out of waterways

## 13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

## 14. TRANSPORTATION INFORMATION

**DOT Proper Shipping Name:** Flammable liquids, N.O.S. (2-propanol, **PACKING GROUP:** II

Acetone) GUIDE NUMBER: 128

HAZARD CLASS: 3 DOT CLASS: Flammable liquid

UN NUMBER: UN 1993

# 15. REGULATORY INFORMATION

All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

## 16. OTHER INFORMATON

HMIS INFORMATION: HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0 PROTECTIVE: H

**SARA Title III Information:** 

SARA 302: To the best of our knowledge, none of the chemicals in this product are listed as an Extremely Hazardous Substance under

Section 302 of SARA Title III nor does this product contain any other such substances.

SARA 311/312: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

SARA 313: Propylene glycol monomethyl ether (107-98-2) may be reportable under glycols.

Supplemental Health Info.: In Response to a TSCA test rule, several studies of isopropanol (IPA) have been completed. The studies and their results are as

follows: 1) Both mutagenicity studies, the mouse mononucleus and CHD assays, were negative. 2) Rat and rabbit oral teratogenicity and developmental toxicology: A) There was no evidence that IPA caused teratogenicity in rats or rabbits. B) Developmental toxicity was seen in rats at 1200 mg/kg (evidenced by decrease body weight\*\*) while no developmental toxicity was seen in the rabbit study. For rats, the NOAEL was 400 mg/kg; for rabbits, 480 mg/kg. This work also identified pregnant

rabbits to be approximately eight times more sensitive to IPA's lethal effects than non-pregnant rabbits\*\*.

Other test rule related studies: 3) Rat oral reproductive toxicity: in the rat reproductive toxicity study, the NOAEL for reproduction indices was 1000 mg/kg, however, there was a marked increase in post-weaning pup mortality at this level\*\*. The NOAEL for this effect was 500 mg/kg. Also, the NOAEL for parental female body weight decrease was 100 mg/kg. 4) In adults (max dose 5000 ppm) or offspring (max dose 1200 mg/kg). 5) Subchronic rat and mouse inhalation toxicity. The subchronic NOAEL was 500 ppm based on clinical signs of CNS depression (both species) and increased body weight and blood effects (rat only) seen at 1500 ppm. (note: The information tagged by "\*\*" above were submitted to EPA under the

requirements of TSCA: 8(e).)

N/A = Not Applicable NDA = No Data Available

## Disclaimer

This information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.

3009 Page 4 of 4