MATERIAL SAFETY DATA SHEET

INKSOL 9010

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Tarr, Inc.

4115 W. Turney Avenue

Phoenix, AZ 85019

INFORMATION PHONE: (602) 233-2000

EMERGENCY PHONE: CHEMTREC 800-424-9300 (US) Day or night

International Call Collect CHEMTREC 202-483-7616

Portland, Oregon Phoenix, Arizona

Auburn, Washington

Vancouver, Washington

Print Date: 10/29/2004

PRODUCT NAME: INKSOL 9010

PRODUCT NUMBER: 4066

UPC NUMBER:

PREPARED BY: Patricia Rodabaugh

DATE PREPARED: 10/2/2000 **LAST REVISION:** 10/2/2000

SYNONYMS:

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS # Weight % OSHA PEL ACGIH TLV NOTE

n-Propanol 71-23-8 82-89 200 ppm 200 ppm

n-Propyl acetate 109-60-4 11-18 200 ppm 200 ppm

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Moderately irritating to the eyes.

INHALATION: May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS)

depression.

INGESTION: Irritating to the gastrointestinal tract, causing abdominal pain and vomiting, sometimes bloody. Ingestion may casue

CNS depression, low blood pressure, rapid heart beat and liver damage.

SKIN CONTACT: Mildly irritating to the skin.

SIGNS AND SYMPTOMS OF EXPOSURE:

Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea: In extreme cases, unconsciousness and death may occur. Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation

persists, get medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention.

INGESTION: Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce

4066 Page 1 of 4

vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's head below hips while vomiting. Call doctor.

SKIN CONTACT: Flush skin with water. If irritation occurs, get medical attention.

AGGRAVATED MEDICAL CONDITIONS:

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impared function from preexsiting disorders may be aggravated by exposure to this product.

SUPPLEMENTAL HEALTH INFORMATION:

None identified

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 64 F FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: N/A LEL: 0.017 UEL: 0.137

EXTINGUISHING MEDIA:

Use water fog, "alcohol" foam, dry chemical, or CO2.

SPECIAL FIRE FIGHTING PROCEDURES:

WARNING. Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

COMBUSTION PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANLDING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-suppling respir. of an air-purifying respir. for organic vapors.

VENTILATION:

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PROTECTIVE GLOVES:

Test data indicate the best protection is provided by neoprene, nitrile, and natural rubber gloves.

4066 Page 2 of 4

EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

ENGINEERING CONTROLS:

Facilities storing or utilizing this material should be equipped with and eyewash facility and a safety shower.

EXPOSURE GUIDELINES:

Avoid prolonged or repeated breathing of vapors

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUBILITY IN WATER: Infinite in water

APPEARANCE AND ODOR: Colorless, clear liquid. Mild odor.

BOILING POINT: 206 F **PERCENT VOLATILE:** 100

VAPOR PRESSURE: 15 mmHg @ 20 C PH: N/A

EVAPORATION RATE: Slower than ether **MOLECULAR WEIGHT:** N/A

POUNDS PER GALLON: 6.78 VAPOR DENSITY: Heavier than air

SPECIFIC GRAVITY: 0.814 OTHER PROPERTIES: VOCs:6.78lbs/gal,812.5252g/L

MELTING POINT: -127 FREEZING POINT: N/A

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment

at temperatures above 120 deg. F.

INCOMPATIBILITY:

Strong oxidizers.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition. Do not store or handle in aluminum equipment at temperatures ab

11. TOXICOLOGY INFORMATION

N/A

12. ECOLOGICAL INFORMATION

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

4066 Page 3 of 4

13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name: Flammable liquids, n.o.s. (n-propanol, n- **PACKING GROUP:** II

propyl acetate) GUIDE NUMBER: 128

HAZARD CLASS: 3 DOT CLASS: Flammable liquid

UN NUMBER: UN 1993

15. REGULATORY INFORMATION

This product is listed on the EPA/TSCA inventory of chemical substances. Per 40 CFR part 82, this product does not contain nor was it directly manufactured with any class I or class II ozone depleting substance.

16. OTHER INFORMATON

HMIS INFORMATION: HEALTH: 1 FLAMMABILITY: 3 REACTIVITY: 0 PROTECTIVE: G

SARA Title III Information:

SARA 302: To the best of our knowledge, none of the chemicals in this product are listed as an Extremely Hazardous Substance under

Section 302 of SARA Title III nor does this product contain any other such substances.

SARA 311/312: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

SARA 313: To the best of our knowledge, none of the chemicals in this product are listed as a toxic chemical.

HAP content: None Evap Rate: 1.06

N/A = Not Applicable NDA = No Data Available

Disclaimer

The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr, Incorporated makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Tarr, Inc. assumes no responsibility for injuries from the use of the product described herein.

4066 Page 4 of 4