

SAFETY DATA SHEET GINGER TINCTURE

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: GINGER TINCTURE

PART No.: RM113

APPLICATIONS: The scope of this SDS is applicable to ginger tincture strong and ginger tincture weak.

SUPPLIER: J M Loveridge plc

Southbrook Road, Southampton

Hampshire SO15 1BH

Tel: 023 8022 2008 Fax: 023 8022 2117

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME

CAS No.: EINECS Nr.: CLASSIFICATION

ETHANOL 60-100 %

64-17-5 200-578-6 F R-11

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS: Preparations contain 84 - 95% ethanol (v/v).

3. HAZARDS IDENTIFICATION:

Highly flammable.

4. FIRST AID MEASURES:

GENERAL: IN ALL CASES OF DOUBT OR WHEN SYMPTOMS PERSIST, ALWAYS SEEK

MEDICAL ATTENTION

INHALATION: Move affected person to fresh air. If recovery not rapid, seek medical attention.

INGESTION: DO NOT INDUCE VOMITING. In case of spontaneous vomiting, be sure that vomit

can freely drain because of danger of suffocation. Only when conscious, rinse mouth with plenty of water and give plenty of water to drink - (approx 500 ml). Keep patient at

rest and obtain medical attention.

SKIN: Remove contaminated clothing. Wash affected area with plenty of soap and water. If

irritation persists, seek medical attention. \\

EYES: Rinse immediately with copious amounts of water. If irritation or discomfort persists,

seek medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc.

Halon.

SPECIAL FIRE FIGHTING

PROCEDURES:

Use gentle application of water spray to keep exposed containers cool or to dissipate

vapour.

UNUSUAL FIRE & EXPLOSION

HAZARDS:

May explode when heated or when exposed to flames or sparks. Vapour may travel

considerable distance to source of ignition and flash back.

HAZARDOUS COMBUSTION

PRODUCTS:

Burning will produce oxides of carbon.

PROTECTIVE MEASURES IN FIRE: Fire fighters should wear self-contained breathing apparatus.

6. A CCIDENTAL RELEASE MEASURES:

PERSONAL PRECAUTION IN SPILL: Wear appropriate protective clothing. Eliminate all sources of ignition.

PRECAUTIONS TO PROTECT

ENVIRONMENT:

Prevent contamination of soil, drains and surface water.

SPILL CLEAN UP METHODS: Take-up spillage with absorbent, inert material and place in a suitable and closable

labelled container for recovery or disposal. Wash the area clean with water and

detergent, observing environmental requirements.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: HANDLING - Product should be used in accordance with good industrial principles for

handling and storing of hazardous chemicals.

Spillages will create a fire hazard. Avoid vapour formation and ignition sources. Avoid inhalation of vapours. Ensure good ventilation and local exhaust extraction in work place. (engineering controls must be to explosion/flameproof standard). Earth container and transfer equipment to eliminate accumulation of static charge.

STO RAGE PRECAUTIONS: Store in a cool, dry, well ventilated place, in securely closed original container.

Flammable/combustible - Keep away from oxidising agents, heat and flames.

STO RAGE CRITERIA: Flammable liquid storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME: CAS No.: STD LT EXP 8 Hrs ST EXP 15 Min

ETHANOL 64-17-5 OES 1000 ppm No std.

VENTILATION: Provide adequate general and local exhaust ventilation. Work in fume cupboard.

RESPIRATORS: For short periods of work, a suitable RPE fitted with a combination charcoal or organic

vapour cartridge is recommended.

PROTECTIVE GLOVES: Use impervious gloves made of butyl rubber or PVC.

EYE PROTECTION: Approved chemical safety goggles or face protection.

OTHER PROTECTION: Use engineering controls to reduce air contamination to permissible exposure level.

Wear personal protective equipment appropriate to the quantity of material handled.

HY GIENIC WORK PRACTICES: SKIN PROTECTION - apply barrier cream to hands and exposed skin.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Amber to dark brown mobile liquid.

ODOUR/TASTE: Characteristic, alcoholic odour.

BOILING POINT (°C, interval): ~ 78 Pressure:

DENSITY/SPECIFIC GRAVITY (g/ml): ~ 0.83 - 0.85 Temperature (°C): 20

VAPOUR PRESSURE: 5.81 kPa Temperature (°C): 20

EVAPORATION RATE: 3.4 Reference: BuAc=1

VOLATILE BY VOL. (%): 97

SOLUBILITY DESCRIPTION: Miscible with water.

FLASH POINT (°C): ~ 17 Method: CC (Closed cup).

AUTO IGNITION TEMP. (°C): ~ 365

FLAMMABILITY LIMIT - 3.3 (ethanol)

LOWER(%):

FLAMMABILITY LIMIT - UPPER(%): 19 (ethanol)

10. STABILITY AND REACTIVITY:

STABILITY: Stable under normal conditions of use.

CONDITIONS TO A VOID: Avoid heat, flames and other sources of ignition. Avoid accumulation of static

electricity.

MATERIALS TO AVOID: Sulphuric acid, Nitric acid.

HAZARDOUS DECOMP. PRODUCTS: Thermal decomposition or burning will release oxides of carbon.

11. TOXICOLOGICAL INFORMATION:

TOXIC DOSE - LD 50: Ethanol - 7060 mg/kg (oral rat)

HEALTH HAZARDS, GENERAL: Intoxicating if inhaled or ingested.

INHALATION: May cause transient irritation to the respiratory system. Exposure to high vapour

concentration may cause central nervous system depression or systemic effects similar

to those of ingestion.

INGESTION: May cause nausea, vomiting, dizziness and depression of CNS.

Aspiration during swallowing or vomiting may severely damage the lungs.

SKIN: Repeated or prolonged contact may cause mild irritation and/or drying (defatting) of

skın.

EYES: May cause transient eye irritation or damage.

OTHER HEALTH EFFECTS: For ethanol, adverse effects on male reproductive system have been reported in

laboratory animals on prolonged exposure.

Inconsistent mutagenic activity has been reported.

ROUTE OF ENTRY: Inhalation.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION: Regarded as having low toxicity to aquatic organisms. - ethanol.

MOBILITY: Water soluble, will partition to aqueous phase. Lost within short period through

evaporation and dissolution. Poorly absorbed onto soils or sediments. - ethanol.

BIO ACCUMULATION: Low bioaccumulation potential. - ethanol.

DEGRAD ABILITY: Readily biodegradable. For ethanol - BOD5 = 37.74% of ThOD; BOD20 = 75-84% of

ThOD.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: This material and/or its container must be disposed of as hazardous waste according to

Special Waste Regulations 1996 or according to local regulations, in compliance with

Duty of Care Regulations and Special Waste Regulations.

WASTE CLASS: WASTE CODE:0705** HAZARDOUS PROPERTY: H3-A

14. TRANSPORT INFORMATION:

ADR CLASS No.: 3

ADR CLASS: Class 3: Flammable liquids.

ADR ITEM No.: 3°(b)

HAZARD No. (ADR): 33 Highly flammable liquid (flash-point below 23°C).

ADR MARGINAL: 2301

ADR LABEL No.: 3

HAZCHEM CODE: 2YE

PROPER SHIPPING NAME I: TINCTURES, MEDICINAL

ROAD TRANSPORT NOTES: Flash point: 17°C

UN No. SEA: UN 1293

IM DG CLASS: 3.2

IM DG PAGE No.: 3284

IM DG PACK GR .:

UN No., AIR: UN-ID 1293

ICAO CLASS:

AIR PACK GR.:

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES: R-11 Highly flammable.

SAFETY PHRASES: S-16 Keep away from sources of ignition - No Smoking.

S-9 Keep container in a well ventilated place.

UK REGULATORY REFERENCES: Classification, Packaging and Labelling Regulations 1984. Chemicals (Hazard

Information & Packaging) Regulations 1993.

16. OTHER INFORMATION:

SDS No .:

INFORMATION SOURCES: This product has been classified in accordance with CHIP3 regulations.

REVISION COMMENTS: Edition 01; Revised item(s):

215

ISSUED BY: MK

DATE: 12/07/02

DISCLAIMER: The foregoing data has been compiled for safety information only and does not form

part of any selling specification. Information contained in this Data Sheet is to the best of JMLs knowledge correct at the time of publication. Customers should always satisfy themselves, that the product which they have selected is entirely suitable for their purpose under their conditions of use and in compliance with current regulations. For

any further information, please contact the supplier.

R-PHRASES (Full Text): R-11 Highly flammable.