MATERIAL SAFETY DATA SHEET

|-----SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

: PRIMER 67DTO COMP. B

PREPARE / REVISED: 10/19/2011 IDENTIFICATION NUMBER: PR67DTOB000B

PRODUCT USE/CLASS : EPOXY HARDENER

SUPPLIER: MANUFACTURER: Dudick, Inc. Dudick, Inc.

1818 Miller Parkway 1818 Miller Parkway Streetsboro, Ohio 44241 Streetsboro, Ohio 44241

CHEM-TEL: 800-255-3924 CHEM-TEL: 800-255-3924

24 HOURS A DAY 24 HOURS A DAY

PREPARER: DUDICK, INC., PHONE: 800-322-1970

=======================================
SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

WT/WT %

ITEM	CHEMICAL NAME	CAS NUMBER	LESS THAN
01	REACTION PRODUCTS WITH TEPA	68953-36-6	80.0 %
02	TETRAETHYLENEPENTAMINE	112-57-2	15.0 %
03	DIMETHYLAMINOPROPYLAMINE	109-55-7	10.0 %
04	CARBON	1333-86-4	0.1 %

 EXPOSURE	LIMITS	

	ACGI	H	OSHA	7	COMPANY	
ITEM	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	NE	NE	NO INFO	NO INFO	NE	YES
02	NE	NE	NO INFO	NO INFO	NE	YES
03	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
04	3.5 mg/m3	NO INFO	3.5 mg/m3	NO INFO	NE	NO

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION	

*** EMERGENCY OVERVIEW ***: DANGER!---CAUSES BURNS. HARMFUL IF SWALLOWED. DO NOT GET IN EYES, ON SKIN, OR CLOTHING. DO NOT BREATH VAPORS OR MISTS.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: EYE CONTACT MAY CAUSE SEVERE IRRITATION WITH CORNEAL INJURY. MAY CAUSE BLINDNESS.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: SEVERE SKIN IRRITANT.

(Continued on Page 2)

	========	GEOGRAN	=========		=======
	=========	SECTION :	3 - HAZARDS ========	IDENTIFICATION ====================================	 -==========

EFFECTS OF OVEREXPOSURE - INHALATION: MAY CAUSE IRRITATION OF THE NOSE, THROAT, AND LUNGS. VAPORS AND MISTS MAY BE CORROSIVE TO THE RESPIRATORY

EFFECTS OF OVEREXPOSURE - INGESTION: INGESTION MAY CAUSE BURNS TO THE MOUTH, THROAT, AND ESOPHAGUS. INGESTION MAY CAUSE NAUSEA, CRAMPS, VOMITING, AND DIARRHEA.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: ALLERGIC REACTIONS MAY OCCUR IN SOME INDIVIDUALS. PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT. MAY CAUSE SKIN SENSITIZATION.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

I		==	==			
ĺ	SECTION	4	-	FIRST	AID	MEASURES
I		==	==			

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SUPPLEMENTAL OXYGEN MAY BE INDICATED. CALL A PHYSICIAN.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GIVE VICTIM PLENTY OF WATER TO DRINK IF CONSCIOUS.

	=======================================	===	==	=====		
ĺ	SECTION	5	-	FIRE	FIGHTING	MEASURES
	=======================================	===	==			

FLASH POINT: 160 F LOWER EXPLOSIVE LIMIT: N.A. (SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: MAY PRODUCE TOXIC CARBON MONOXIDE AND NITROGEN OXIDES UPON COMBUSTION.

SPECIAL FIREFIGHTING PROCEDURES: EVACUATE AREA. WATER MAY BE INEFFECTIVE BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

(Continued on Page 3)

	=========	:=========	========		:===============	====	
ĺ	İ	SECTION 6 - 2	ACCIDENTAL	RELEASE	MEASURES	į	
		:=========	========		:======================================	====	
	Product: PR	R67DTOB000B	PREPARE /	REVISED:	10/19/2011	Page	3

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA TO CONTAIN SPILLAGE. ABSORB EXCESS WITH SAND, EARTH, OR VERMICULITE. SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS.

|-----| SECTION 7 - HANDLING AND STORAGE |-----|

HANDLING: IF BODILY CONTACT OCCURS, REMOVE CONTAMINATED CLOTHING AT ONCE. AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING VAPORS. FOR INDUSTRIAL USE ONLY. WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

STORAGE: DO NOT STORE NEAR INCOMPATIBLES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

|-----SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION |-----|

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR WHEN EXPOSURE TO MISTS OR VAPORS IS LIKELY.

SKIN PROTECTION: IMPERVIOUS RUBBER OR NEOPRENE TYPE. CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED AS MINIMUM PROTECTION. GOGGLES RECOMMENDED FOR INDIVIDUALS MIXING THE RESIN AND CATALYST.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

|-----| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : 275 - 7592 F VAPOR DENSITY : Is heavier than air

ODOR THRESHOLD : NE

ODOR : AMINE ODOR THRESHOLD : NE APPEARANCE : BLACK LIQUID EVAPORATION RATE: Is slower than Ether

SOLUBILITY IN H2O : PARTIAL

SPECIFIC GRAVITY: 0.936 FREEZE POINT : NE VAPOR PRESSURE : NE рн @ 0.0 % : NE

PHYSICAL STATE : LIQUID VISCOSITY : 150-250cps

COEFFICIENT OF WATER/OIL DISTRIBUTION: NE

(See Section 16 for abbreviation legend)

(Continued on Page 4) ______

Product: PR67DTOB000B	
SECTION 10 - STABILITY AND REACTIVE	!
SECTION TO STABILITY AND REACTIVE	-
CONDITIONS TO AVOID: HEAT, FLAME, CONTAMINANTS.	
INCOMPATIBILITY: STRONG OXIDANTS. STRONG ACIDS.	
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF NITROGEN OTHER TOXIC ORGANIC SUBSTANCES MAY BE FORMED. COMBUSINCLUDE NITRILES AND AMIDES.	
HAZARDOUS POLYMERIZATION: Will not occur under normal	conditions.
STABILITY: This product is stable under normal storage	ge conditions.
SECTION 11 - TOXICOLOGICAL PROPERTI	ES
No product or component toxicological information is	available.
	=======
SECTION 12 - ECOLOGICAL INFORMATIO	ON
=======================================	
ECOLOGICAL INFORMATION: DO NOT CONTAMINATE PONDS, ST WATER SUPPLY.	
GROWTON 12 PROPERTY GOVERNMENT	
SECTION 13 - DISPOSAL CONSIDERATIO	<u> </u>
DISPOSAL METHOD: FOLLOW ALL RELEVANT LOCAL, STATE, A REGULATIONS. EMPTY DRUMS MAY CONTAIN RESIDUE OR FUME ALTHOUGH THIS PRODUCT WOULD NOT BE A RCRA HAZARDOUS W LANDFILL DISPOSAL MAY PRESENT LONG TERM ENVIRONMENTAI	ES WHICH ARE HARMFUL. NASTE IF DISPOSED,
SECTION 14 - TRANSPORTATION INFORMAT	-
DOT PROPER SHIPPING NAME: CORROSIVE LIQUID N.O.S.	
DOT TECHNICAL NAME: POLYAMINES	
DOT HAZARD CLASS: 8 HAZARD SUE	BCLASS: NA
DOT UN/NA NUMBER: UN1760 PACKING GROUP: II	RESP. GUIDE PAGE: 154
SECTION 15 - REGULATORY INFORMATIO	:
THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING	G IN SECTION 2:
CHEMICAL NAME CAS NUMBER No non-hazardous components exist	WT/WT % IS LESS THAN
10 101 Hazaraoab components carst	
	(Continued on Page 5)

Product: PR67DTOB000B PREPARE / REVISED: 10/19/2011 Page 5
=====================================
U.S. FEDERAL REGULATIONS: AS FOLLOWS -
OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)
CERCLA - SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:
IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD
SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
CHEMICAL NAME CAS NUMBER WT/WT % IS LESS THAN No SARA Section 313 components exist in this product.
TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are not on the TSCA Section 8 Inventory.
This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:
CHEMICAL NAME CAS NUMBER No information is available.
U.S. STATE REGULATIONS: AS FOLLOWS -
NEW JERSEY RIGHT-TO-KNOW: The following materials are non-hazardous, but are among the top five components in this product:
CHEMICAL NAME CAS NUMBER No non-hazardous materials are among the top five ingredients.
PENNSYLVANIA RIGHT-TO-KNOW: The following non-hazardous ingredients are present in the product at greater than 3%:
CHEMICAL NAME CAS NUMBER No non-hazardous ingredients are present at greater than 3%.
CALIFORNIA PROPOSITION 65:

(Continued on Page 6)

Product: PR67DTOB000B PREPARE / REVISED: 10/19/2011	Page	6
	====	
SECTION 15 - REGULATORY INFORMATION		
	====	

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: E

HMIS RATINGS - HEALTH: 3* FLAMMABILITY: 2 REACTIVITY: 0

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.47 lbs/gal, 56 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,

N.D. - Not Determined

The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.
