

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 18-Mar-2015

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Static Guard

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Anti-Static Product - Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name B&G Foods, Inc.
Supplier Address Four Gatehall Drive
Suite 110
Parsippany
New Jersey
07054
US
Supplier Phone Number Phone:(800) 288-2303
Fax:(973) 630-6550
Contact Phone(973) 630-6414
Supplier Email bwright@bgfoods.com
Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements



Emergency Overview

Signal word		Danger	
Hazard Statements			
Causes serious eye irritation			
May cause an allergic skin reaction			
Extremely flammable aerosol			
Contains gas under pressure; may explode if heated			
			
Appearance	Clear	Physical State	Liquid spray Aerosol
		Odor	Typical alcohol odor

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Pressurized container: Do not pierce or burn, even after use
 Do not spray on an open flame or other ignition source

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place
 Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

20.5% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects
 Toxic to aquatic life
 Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Alcohol	64-17-5	60 - 100	*
Isobutane	75-28-5	3 - 7	*
Propane	74-98-6	1 - 5	*
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, chlorides	61789-80-8	1 - 5	*
Fragrance (May cause sensitization by skin contact)	Fragrance	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin Contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation

Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Keep victim warm and quiet.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Uniform Fire Code

Sensitizer: Liquid

Aerosols: Level III

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information

Ventilate the area.

Environmental Precautions

Environmental Precautions

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment

If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for cleaning up

Do not direct water at spill or source of leak.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Keep tightly closed in a dry and cool place. Keep in properly labeled containers.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m ³
Isobutane 75-28-5	STEL: 1000 ppm	N/A	N/A
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health NIOSH IDLH

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and Body Protection Wear protective gloves and protective clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid spray, Aerosol		
Appearance	Clear	Odor	Typical alcohol odor
Color	No information available	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Soluble in water	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing Properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Alcohol 64-17-5	-	-	= 124.7 mg/L (Rat) 4 h
Isobutane 75-28-5	-	-	= 658 mg/L (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, chlorides 61789-80-8	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 180 mg/L (Rat) 1 h

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Itching. Rashes. Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Alcohol 64-17-5	A3	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied. Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

Target Organ Effects Eyes. Skin. Blood. Central Nervous System (CNS). Liver. Reproductive System. Respiratory system. Heart.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-gas)

2,739,001.00

ATEmix (inhalation-dust/mist)

132.20 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Alcohol 64-17-5		96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 13400 - 15100 mg/L (Pimephales promelas) 96h LC50: 12.0 - 16.0 mL/L (Oncorhynchus mykiss)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	48h LC50: 9268 - 14221 mg/L 48h EC50: = 2 mg/L 24h EC50: = 10800 mg/L
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, chlorides 61789-80-8	72h EC50: = 0.00046 mg/L (Pseudokirchneriella subcapitata) 96h EC50: = 0.1 mg/L (Desmodesmus subspicatus)	96h LC50: = 1.48 mg/L (Brachydanio rerio)		48h EC50: = 0.32 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Alcohol 64-17-5	-0.32
Isobutane 75-28-5	2.88
Propane 74-98-6	2.3

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.
US EPA Waste Number	D001

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Alcohol 64-17-5	Toxic Ignitable

14. TRANSPORT INFORMATION



DOT

Proper Shipping Name	CONSUMER COMMODITY
Hazard Class	ORM-D
Description	CONSUMER COMMODITY, ORM-D
Emergency Response Guide Number	126

TDG

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

MEX

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

ICAO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Description	UN1950, AEROSOLS, 2.1

IATA

UN-No.	UN1950
Proper Shipping Name	AEROSOLS, FLAMMABLE
Hazard Class	2.1
Description	UN1950, AEROSOLS, FLAMMABLE, 2.1

IMDG/IMO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
EmS-No.	F-D, S-U
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
Description	UN1950, AEROSOLS, 2.1

RID

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F
Description	UN1950, AEROSOLS, 2.1

ADR

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F
Tunnel restriction code	(D)
Description	UN1950, AEROSOLS, 2.1

ADN

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.1
Classification code	5F

Special Provisions	190, 327, 344, 625
Description	UN1950, AEROSOLS, 2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Alcohol - 64-17-5	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Alcohol 64-17-5	X	X	X		
Hydrofluorocarbon 152a 75-37-6	X	X			
Isobutane 75-28-5	X	X	X		
Propane 74-98-6	X	X	X		

International Regulations



Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Alcohol 64-17-5 (60 - 100)		Mexico: TWA= 1900 mg/m ³ Mexico: TWA= 1000 ppm

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

D2A - Very toxic materials

A - Compressed gases

B5 - Flammable aerosol



16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 4	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 2	Flammability 4	Physical Hazard 0	Personal Protection X

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501
 Revision Date 18-Mar-2015
 Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet