

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Innershield® NR®-208-H

Product Size: 5/64 in.

Other means of identification

SDS number: 200000000128

Recommended use and restriction on use

Recommended use: FCAW-S (Self-Shielded Flux Cored Arc Welding)

Restrictions on use: Not known. Read this SDS before using this product.

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer/Supplier:

The Lincoln Electric Company
22801 Saint Clair Avenue
Cleveland, Ohio 44117 USA
Phone: +1 (216) 481-8100

The Lincoln Electric Company of Canada LP
179 Wicksteed Avenue
Toronto, Ontario M4G 2B9 CANADA
Phone: +1 (416) 421-2600

Safety Data Sheet Questions: SDS@lincolnelectric.com

Arc Welding Safety Information: www.lincolnelectric.com/safety

24-Hour Emergency Response Telephone Numbers:

<u>Area</u>	<u>Telephone</u>
USA/Canada/Mexico	+1 (888) 609-1762
Americas/Europe	+1 (216) 383-8962
Asia Pacific	+1 (216) 383-8966
Middle East/Africa	+1 (216) 383-8969

3E Company Access Code: 333988

2. HAZARDS IDENTIFICATION

Classified according to the criteria of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Controlled Products Regulations.

Hazard Classification Not classified as hazardous according to applicable GHS hazard classification criteria.

Label Elements

Hazard Symbol:	No symbol
Signal Word:	No signal word.
Hazard Statement	Not applicable

Precautionary Statement

Not applicable

Other hazards which do not result in GHS classification:

Electrical Shock can kill. If welding must be performed in damp locations or with wet clothing, on metal structures or when in cramped positions such as sitting, kneeling or lying, or if there is a high risk of unavoidable or accidental contact with work piece, use the following equipment: Semiautomatic DC Welder, DC Manual (Stick) Welder, or AC Welder with Reduced Voltage Control.

Arc rays can injure eyes and burn skin. Welding arc and sparks can ignite combustibles and flammable materials. Overexposure to welding fumes and gases can be hazardous. Read and understand the manufacturer's instructions, Safety Data Sheets and the precautionary labels before using this product. Refer to Section 8.

Substance(s) formed under the conditions of use:

The welding fume produced from this welding electrode may contain the following constituent(s) and/or their complex metallic oxides as well as solid particles or other constituents from the consumables, base metal, or base metal coating not listed below:

Chemical Identity	CAS-No.
Carbon dioxide	124-38-9
Carbon monoxide	630-08-0
Nitrogen dioxide	10102-44-0
Ozone	10028-15-6
Manganese	7439-96-5
Barium and soluble compounds (as Ba)	7440-39-3
Nickel	7440-02-0
Fluorides (as F)	16984-48-8

3. COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Ingredients

Chemical Identity	CAS number	Content in percent (%)*
Iron	7439-89-6	60 - 100%
Barium fluoride	7787-32-8	7 - 13%
Iron oxide	1309-37-1	1 - 5%
Manganese	7439-96-5	1 - 5%
Aluminum and/or aluminum alloys (as Al)	7429-90-5	1 - 5%
Lithium fluoride	7789-24-4	1 - 5%
Magnesium	7439-95-4	1 - 5%
Nickel	7440-02-0	0.5 - 1.5%
Lithium oxide	12057-24-8	0.5 - 1.5%
Silicon dioxide (amorphous)	7631-86-9	0.1 - 1%
Calcium oxide	1305-78-8	0.1 - 1%
Zirconium alloys and compounds (as Zr)	7440-67-7	0.1 - 1%
Potassium fluorosilicate	16871-90-2	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments:

The term "Hazardous Ingredients" should be interpreted as a term defined in Hazard Communication standards and does not necessarily imply the

existence of a welding hazard. The product may contain additional non-hazardous ingredients or may form additional compounds under the condition of use. Refer to Sections 2 and 8 for more information.

4. FIRST AID MEASURES

- Ingestion:** Unlikely due to form of product, except for granular materials. Avoid hand, clothing, food, and drink contact with metal fume or powder which can cause ingestion of particulate during hand to mouth activities such as drinking, eating, smoking, etc. If ingested, do not induce vomiting. Contact a poison control center. Unless the poison control center advises otherwise, wash out mouth thoroughly with water. If symptoms develop, seek medical attention at once.
- Inhalation:** Move to fresh air if breathing is difficult. If breathing has stopped, perform artificial respiration and obtain medical assistance at once.
- Skin Contact:** Remove contaminated clothing and wash the skin thoroughly with soap and water. For reddened or blistered skin, or thermal burns, obtain medical assistance at once.
- Eye contact:** Dust or fume from this product should be flushed from the eyes with copious amounts of clean, tepid water until transported to an emergency medical facility. Do not allow victim to rub or keep eyes tightly closed. Obtain medical assistance at once.
- Arc rays can injure eyes. If exposed to arc rays, move victim to dark room, remove contact lenses as necessary for treatment, cover eyes with a padded dressing and rest. Obtain medical assistance if symptoms persist.

Most important symptoms/effects, acute and delayed

- Symptoms:** Short-term (acute) overexposure to welding fumes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema).
- Long-term (chronic) overexposure to welding fumes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects. Refer to Section 11 for more information.

- Hazards:** Welding hazards are complex and may include physical and health hazards such as but not limited to electric shock, physical strains, radiation burns (eye flash), thermal burns due to hot metal or spatter and potential health effects of overexposure to welding fume or dust. Refer to Section 11 for more information.

Indication of immediate medical attention and special treatment needed

- Treatment:** Treat symptomatically.

5. FIRE-FIGHTING MEASURES

- General Fire Hazards:** As shipped, this product is nonflammable. However, welding arc and sparks can ignite combustibles and flammable products. Read and understand American National Standard Z49.1, "Safety In Welding, Cutting and Allied Processes" and National Fire Protection Association NFPA 51B, "Standard for Fire Prevention During Welding, Cutting and Other Hot Work" before using this product.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: As shipped, the product will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.

Unsuitable extinguishing media: None known.

Specific hazards arising from the chemical: Welding arc and sparks can ignite combustibles and flammable products.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: Use standard firefighting procedures and consider the hazards of other involved materials.

Special protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures If airborne dust and/or fume is present, use adequate engineering controls and, if needed, personal protection to prevent overexposure. Refer to recommendations in Section 8.

Methods and material for containment and cleaning up Clean up spills immediately, observing precautions in the personal protective equipment in Section 8. Avoid generating dust. Prevent product from entering any drains, sewers or water sources. Refer to Section 13 for proper disposal.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed.

Read and understand the manufacturer's instruction and the precautionary label on the product. Refer to Lincoln Safety Publications at www.lincolnelectric.com/safety. See American National Standard Z49.1, "Safety In Welding, Cutting and Allied Processes" published by the American Welding Society, <http://pubs.aws.org> and OSHA Publication 2206 (29CFR1910), U.S. Government Printing Office, www.gpo.gov.

Conditions for safe storage, including any incompatibilities: Store in closed original container in a dry place. Store away from incompatible materials. Store in accordance with local/regional/national regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits: US

Chemical Identity	Type	Exposure Limit Values	Source
Barium fluoride - as Ba	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Barium fluoride - as F	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Barium fluoride - as Ba	REL	0.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Barium fluoride - as F	REL	2.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Barium fluoride - as Ba	PEL	0.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium fluoride - as F	PEL	2.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium fluoride - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Dust and fume. - as Fe	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Manganese - Fume. - as Mn	Ceiling	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Manganese - Inhalable fraction. - as Mn	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Manganese - Respirable fraction. - as Mn	TWA	0.02 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Aluminum and/or aluminum alloys (as Al) - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Aluminum and/or aluminum alloys (as Al) - Respirable dust. - as Al	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum and/or aluminum alloys (as Al) - Total dust. - as Al	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum and/or aluminum alloys (as Al) - Welding fume or pyrophoric powder. - as Al	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Aluminum and/or aluminum alloys (as Al) - Respirable.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Aluminum and/or aluminum alloys (as Al) - Total	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Lithium fluoride - as F	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	REL	2.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	2.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Lithium fluoride - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Nickel - as Ni	PEL	1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	0.015 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)

Silicon dioxide (amorphous)	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	REL	6 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Zirconium alloys and compounds (as Zr) - as Zr	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	STEL	10 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Potassium fluorosilicate - as F	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	REL	2.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	2.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Potassium fluorosilicate - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)

Occupational Exposure Limits: CANADA

Chemical Identity	Type	Exposure Limit Values	Source
Barium fluoride - as Ba	TWA	0.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Barium fluoride - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Barium fluoride - as Ba	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium fluoride - as F	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
Barium fluoride - as Ba	TWA	0.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
Barium fluoride - as F	TWAEV	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium fluoride - as Ba	TWAEV	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium fluoride - as F	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Barium fluoride - as Ba	8 HR ACL	0.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)

Barium fluoride - as F	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Barium fluoride - as Ba	15 MIN ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Barium fluoride - as F	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium fluoride - as Ba	TWA	0.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Respirable.	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust. - as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume. - as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume. - as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Iron oxide	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Iron oxide - Dust and fume. - as Fe	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Dust and fume. - as Fe	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - as Mn	TWA	0.2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWAEV	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical

			Agents) (11 2010)
	8 HR ACL	0.2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	0.6 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Manganese - Fume. - as Mn	TWA	1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - Dust. - as Mn	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - Fume. - as Mn	STEL	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - Respirable fraction. - as Mn	TWA	0.02 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
Manganese - Inhalable fraction. - as Mn	TWA	0.1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder. - as Al	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Aluminum and/or aluminum alloys (as Al) - Dust.	TWA	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Aluminum and/or aluminum alloys (as Al) - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum and/or aluminum alloys (as Al) - Respirable fraction.	TWA	1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder. - as Al	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Aluminum and/or aluminum alloys (as Al) - Dust. - as Al	8 HR ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder. - as Al	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Aluminum and/or aluminum alloys (as Al) - Dust. - as Al	15 MIN ACL	20 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Aluminum and/or aluminum alloys (as Al)	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum and/or aluminum alloys (as Al) - Welding fume. - as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum and/or aluminum alloys (as Al) - as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Lithium fluoride - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

			(03 2011)
	TWAEV	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Nickel	TWA	1.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.05 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
Nickel - Inhalable - as Ni	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Nickel - Inhalable fraction. - as Ni	8 HR ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Nickel	TWA	1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Silicon dioxide (amorphous) - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Silicon dioxide (amorphous) - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Silicon dioxide (amorphous)	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (07 2010)
Silicon dioxide (amorphous) - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (07 2010)
	15 MIN ACL	4 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	8 HR ACL	2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the

			Work Environment) (12 2008)
Zirconium alloys and compounds (as Zr) - as Zr	STEL	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	10 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWA	5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Potassium fluorosilicate - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Occupational Exposure Limits: MEXICO

Chemical Identity	Type	Exposure Limit Values	Source
Barium fluoride - as Ba	CPT	0.5 mg/m3	Mexico. Occupational Exposure Limit

			Values (03 2000)
Barium fluoride - as F	CPT	2.5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Iron oxide - as Fe	CTT	10 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
	CPT	5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Manganese - as Mn	CPT	0.2 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Manganese - Fume. - as Mn	CPT	1 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
	CTT	3 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Aluminum and/or aluminum alloys (as Al) - Pyrophoric powder.	CPT	5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Aluminum and/or aluminum alloys (as Al) - Dust.	CPT	10 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Aluminum and/or aluminum alloys (as Al) - Welding fume.	CPT	5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Lithium fluoride - as F	CPT	2.5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Nickel	CPT	1 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Silicon dioxide (amorphous)	CPT	10 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Silicon dioxide (amorphous) - Respirable dust.	CPT	3 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Silicon dioxide (amorphous) - Inhalable particulate.	CPT	10 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Calcium oxide	CPT	2 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Potassium fluorosilicate - as F	CPT	2.5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)

Biological Limit Values: US

Chemical Identity	Exposure Limit Values	Source
Barium fluoride (Fluoride: Sampling time: Prior to shift.)	2 mg/l (Urine)	ACGIH BEL (03 2013)
Barium fluoride (Fluoride: Sampling time: End of shift.)	3 mg/l (Urine)	ACGIH BEL (03 2013)
Lithium fluoride (Fluoride: Sampling time: Prior to shift.)	2 mg/l (Urine)	ACGIH BEL (03 2013)
Lithium fluoride (Fluoride: Sampling time: End of shift.)	3 mg/l (Urine)	ACGIH BEL (03 2013)
Potassium fluorosilicate (Fluoride: Sampling time: Prior to shift.)	2 mg/l (Urine)	ACGIH BEL (03 2013)
Potassium fluorosilicate (Fluoride: Sampling time: End of shift.)	3 mg/l (Urine)	ACGIH BEL (03 2013)

Biological Limit Values: MEXICO

Chemical Identity	Exposure Limit Values	Source
Barium fluoride (fluorides: Sampling time: End of shift.)	10 mg/g (Creatinine in urine)	MX IBE (06 2012)
Barium fluoride (fluorides: Sampling time: Prior to shift.)	3 mg/g (Creatinine in urine)	MX IBE (06 2012)
Lithium fluoride (fluorides: Sampling time: End of shift.)	10 mg/g (Creatinine in urine)	MX IBE (06 2012)
Lithium fluoride (fluorides: Sampling time: Prior to shift.)	3 mg/g (Creatinine in urine)	MX IBE (06 2012)

Potassium fluorosilicate (fluorides: Sampling time: Prior to shift.)	3 mg/g (Creatinine in urine)	MX IBE (06 2012)
Potassium fluorosilicate (fluorides: Sampling time: End of shift.)	10 mg/g (Creatinine in urine)	MX IBE (06 2012)

Additional exposure limits under the conditions of use: US

Chemical Identity	Type	Exposure Limit Values	Source
Carbon dioxide	TWA	5,000 ppm	US. ACGIH Threshold Limit Values (12 2010)
	STEL	30,000 ppm	US. ACGIH Threshold Limit Values (12 2010)
	PEL	5,000 ppm 9,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	30,000 ppm 54,000 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	5,000 ppm 9,000 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Carbon monoxide	TWA	25 ppm	US. ACGIH Threshold Limit Values (12 2010)
	PEL	50 ppm 55 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	35 ppm 40 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	Ceil_Time	200 ppm 229 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Nitrogen dioxide	TWA	0.2 ppm	US. ACGIH Threshold Limit Values (02 2012)
	Ceiling	5 ppm 9 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	1 ppm 1.8 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Ozone	PEL	0.1 ppm 0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	Ceil_Time	0.1 ppm 0.2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	0.05 ppm	US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.20 ppm	US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.10 ppm	US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.08 ppm	US. ACGIH Threshold Limit Values (03 2014)
Manganese - Fume. - as Mn	Ceiling	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Manganese - Inhalable fraction. - as Mn	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Manganese - Respirable fraction. - as Mn	TWA	0.02 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Barium and soluble compounds (as Ba) - as Ba	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
Nickel - as Ni	PEL	1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	0.015 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)

Fluorides (as F) - as F	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values (12 2010)
	PEL	2.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Fluorides (as F) - Dust.	TWA	2.5 mg/m3	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)

Additional exposure limits under the conditions of use: CANADA

Chemical Identity	Type	Exposure Limit Values	Source
Carbon dioxide	STEL	30,000 ppm 54,000 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	5,000 ppm 9,000 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	5,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	15,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5,000 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	STEL	30,000 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	STEV	30,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	5,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	5,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	30,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	5,000 ppm 9,000 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	30,000 ppm 54,000 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon monoxide	TWA	25 ppm 29 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	STEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (07 2010)

	TWAEV	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (07 2010)
	8 HR ACL	25 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	190 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	35 ppm 40 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	200 ppm 230 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Nitrogen dioxide	STEL	5 ppm 9.4 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	3 ppm 5.6 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	CEILING	1 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.2 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2012)
	STEV	5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	3 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	3 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	5 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	3 ppm 5.6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ozone	STEL	0.3 ppm 0.6 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.1 ppm 0.2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.05 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.08 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.2 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWAEV	0.1 ppm 0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (07 2010)

	STEV	0.3 ppm 0.6 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (07 2010)
	15 MIN ACL	0.15 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	8 HR ACL	0.05 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	CEILING	0.1 ppm 0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	0.20 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
	TWA	0.05 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
	TWA	0.08 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
	TWA	0.10 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
Manganese - as Mn	TWA	0.2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWAEV	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	0.2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	0.6 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Manganese - Fume. - as Mn	TWA	1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - Dust. - as Mn	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - Fume. - as Mn	STEL	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Manganese - Respirable fraction. - as Mn	TWA	0.02 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
Manganese - Inhalable fraction. - as Mn	TWA	0.1 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2014)
Barium and soluble compounds (as Ba) - as Ba	TWA	0.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	0.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)

	15 MIN ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Nickel	TWA	1.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	0.05 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Nickel - Inhalable fraction.	TWA	1.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
Nickel - Inhalable - as Ni	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Nickel - Inhalable fraction. - as Ni	8 HR ACL	1.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	3 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Nickel	TWA	1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fluorides (as F) - as F	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	TWA	2.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	2.5 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2011)
	TWAEV	2.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	8 HR ACL	2.5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	TWA	2.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Additional exposure limits under the conditions of use: MEXICO

Chemical Identity	Type	Exposure Limit Values		Source
Carbon dioxide	CPT	5,000 ppm	9,000 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
	CTT	15,000 ppm	27,000 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Carbon monoxide	CTT	400 ppm	400 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
	CPT	50 ppm	55 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Nitrogen dioxide	CTT	5 ppm	10 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
	CPT	3 ppm	6 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Ozone	P	0.1 ppm	0.2 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Manganese - as Mn	CPT		0.2 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)

Manganese - Fume. - as Mn	CPT	1 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
	CTT	3 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Nickel	CPT	1 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)
Fluorides (as F) - as F	CPT	2.5 mg/m3	Mexico. Occupational Exposure Limit Values (03 2000)

Appropriate Engineering Controls

Ventilation: Use enough ventilation, local exhaust at the arc, or both to keep the fumes and gases from the worker's breathing zone and the general area. Train the welder to keep his head out of the fumes. **Keep exposure as low as possible.**

Individual protection measures, such as personal protective equipment

General information:

Exposure Guidelines: Threshold Limit Values (TLVs) and Biological Exposure Indices (BEIs) are values published by the American Conference of Government Industrial Hygienists (ACGIH). ACGIH Statement of Positions Regarding the TLVs® and BEIs® states that the TLV-TWA should be used as a guide in the control of health hazards and should not be used to indicate a fine line between safe and dangerous exposures. See Section 10 for information on potential fume constituents of health interest. Threshold Limit Values are figures published by the American Conference of Government Industrial Hygienists.

Maximum Fume Exposure Guideline™ (MFEG)™ for this product (based on content of Manganese) is 0.8 mg/m3. This exposure guideline is calculated using the most conservative value of the ACGIH TLV or OSHA PEL for the stated substance.

Eye/face protection:

Wear helmet or use face shield with filter lens shade number 12 or darker for open arc processes. No specific lens shade recommendation for submerged arc processes. Shield others by providing screens and flash goggles.

Skin Protection

Hand Protection:

Wear protective gloves. Suitable gloves can be recommended by the glove supplier.

Other:

Protective Clothing: Wear hand, head, and body protection which help to prevent injury from radiation, sparks and electrical shock. See Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Wear dry gloves free of holes or split seams. Train the welder not to permit electrically live parts or electrodes to contact skin . . . or clothing or gloves if they are wet. Insulate yourself from the work piece and ground using dry plywood, rubber mats or other dry insulation.

Respiratory Protection:

Keep your head out of fumes. Use enough ventilation and local exhaust to keep fumes and gases from your breathing zone and the general area. An approved respirator should be used unless exposure assessments are below applicable exposure limits.

Hygiene measures:

Do not eat, drink or smoke when using the product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.2, F1.3 and F1.5, available from the American Welding Society, www.aws.org.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Cored welding wire
Physical state:	Solid
Form:	Solid
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	Not applicable
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	Not applicable
Evaporation rate:	Not applicable
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	Not applicable
Vapor density:	Not applicable
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity:	The product is non-reactive under normal conditions of use, storage and transport.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Avoid heat or contamination.

Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
Hazardous Decomposition Products:	<p>Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and electrodes used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders and the volume of the worker area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities.)</p> <p>When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc., as noted above. Reasonably expected fume constituents produced during arc welding include the oxides of iron, manganese and other metals present in the welding consumable or base metal. Hexavalent chromium compounds may be in the welding fume of consumables or base metals which contain chromium. Gaseous and particulate fluoride may be in the welding fume of consumables which contain fluoride. Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc.</p>

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Ingestion:	Health injuries from ingestion are not known or expected under normal use.
Inhalation:	Potential chronic health hazards related to the use of welding consumables are most applicable to the inhalation route of exposure. Refer to Inhalation statements in Section 11.
Skin Contact:	Arc rays can burn skin. Skin cancer has been reported.
Eye contact:	Arc rays can injure eyes.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	Short-term (acute) overexposure to welding fumes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat, or eyes. May aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long-term (chronic) overexposure to welding fumes can lead to siderosis (iron deposits in lung), central nervous system effects, bronchitis and other pulmonary effects.
--------------------	--

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	Not classified
Specified substance(s):	
Iron	LD 50 (Rat): 98.6 g/kg
Barium fluoride	LD 50 (Rat): 250 mg/kg
Lithium fluoride	LD 50 (Rat): 143 mg/kg
Zirconium alloys and	LD 50 (Rat): 3,500 mg/kg

compounds (as Zr)
Potassium fluorosilicate LD 50 (Rat): 114 mg/kg

Dermal

Product: Not classified

Inhalation

Product: Not classified

Specified substance(s):

Aluminum and/or LC 50 (Rat, 1 h): 7.6 mg/l

aluminum alloys (as Al)

Potassium fluorosilicate LC 50 (Rat, 4 h): 2.021 mg/l

Repeated Dose Toxicity

Product: Not classified

Skin Corrosion/Irritation

Product: Not classified

Serious Eye Damage/Eye Irritation

Product: Not classified

Respiratory or Skin Sensitization

Product: Not classified

Carcinogenicity

Product: Arc rays: Skin cancer has been reported.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Nickel Overall evaluation: 2B. Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Nickel Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity**In vitro**

Product: Not classified

In vivo

Product: Not classified

Reproductive Toxicity

Product: Not classified

Specific Target Organ Toxicity - Single Exposure

Product: Not classified

Specific Target Organ Toxicity - Repeated Exposure

Product: Not classified

Aspiration Hazard

Product: Not classified

Other Effects:

Organic polymers may be used in the manufacture of various welding consumables. Overexposure to their decomposition byproducts may result in a condition known as polymer fume fever. Polymer fume fever usually occurs within 4 to 8 hours of exposure with the presentation of flu like symptoms, including mild pulmonary irritation with or without an increase in body temperature. Signs of exposure can include an increase in white blood cell count. Resolution of symptoms typically occurs quickly, usually not lasting longer than 48 hours.

Symptoms related to the physical, chemical and toxicological characteristics under the condition of use

Inhalation:
Specified substance(s):

Manganese

Overexposure to manganese fumes may affect the brain and central nervous system, resulting in poor coordination, difficulty speaking, and arm or leg tremor. This condition can be irreversible.

Barium and soluble compounds (as Ba)

Overexposure to soluble barium compounds may cause severe stomach pain, slow pulse rate, irregular heartbeat, convulsions, and muscle spasms.

Nickel

Nickel and its compounds are on the IARC and NTP lists as posing respiratory cancer risk, and are skin sensitizers with symptoms ranging from slight itch to severe dermatitis.

Additional toxicological Information under the conditions of use:
Acute toxicity
Oral
Specified substance(s):

Barium and soluble compounds (as Ba)

LD 50 (Rat): 630 mg/kg

Fluorides (as F)

LD 50 (Rat): 4,250 mg/kg

Inhalation
Specified substance(s):

Carbon dioxide

LC Lo (Human, 5 min): 90000 ppm

Carbon monoxide

LC 50 (Rat, 4 h): 1,300 mg/l

Nitrogen dioxide

LC 50 (Rat, 4 h): 88 ppm

Ozone

LC Lo (Human, 30 min): 50 ppm

Carcinogenicity
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
Specified substance(s):

Nickel

Overall evaluation: 2B. Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:
Specified substance(s):

Nickel

Reasonably Anticipated to be a Human Carcinogen.

Other Effects:
Specified substance(s):

Barium and soluble compounds (as Ba)

Muscles Gastro-intestinal system

12. ECOLOGICAL INFORMATION
General information:

Contains a substance which causes risk of hazardous effects to the environment.

Ecotoxicity
Acute hazards to the aquatic environment:
Fish
Product:

Not classified.

Specified substance(s):

Aluminum and/or aluminum alloys (as Al)

LC 50 (Grass carp, white amur (Ctenopharyngodon idella), 96 h): 0.21 - 0.31 mg/l

Nickel

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.916 mg/l

Aquatic Invertebrates

Product: Not classified.
Specified substance(s):
Manganese EC50 (Water flea (Daphnia magna), 48 h): 40 mg/l
Nickel EC50 (Water flea (Daphnia magna), 48 h): 1 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: Not classified.

Aquatic Invertebrates

Product: Not classified.

Toxicity to Aquatic Plants

Product: Not classified.

Persistence and Degradability

Biodegradation

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Nickel Zebra mussel (Dreissena polymorpha), Bioconcentration Factor (BCF): 5,000 - 10,000 (Lotic) Bioconcentration factor calculated using dry weight tissue conc

Mobility in Soil: No data available.

Other Adverse Effects: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

General information: The generation of waste should be avoided or minimized whenever possible. When practical, recycle in an environmentally acceptable, regulatory compliant manner. Dispose of non-recyclable products in accordance with all applicable Federal, State, Provincial, and Local requirements.

Disposal Instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

14. TRANSPORT INFORMATION

DOT

UN Number:	
UN Proper Shipping Name:	NOT DG REGULATED
Transport Hazard Class(es)	
Class:	NR
Label(s):	—
Packing Group:	—
Marine Pollutant:	Not regulated.
Special precautions for user:	—

IMDG

UN Number:	
UN Proper Shipping Name:	NOT DG REGULATED
Transport Hazard Class(es)	
Class:	NR
Label(s):	—
EmS No.:	
Packing Group:	—
Marine Pollutant:	Not regulated.
Special precautions for user:	—

IATA

UN Number:	
Proper Shipping Name:	NOT DG REGULATED
Transport Hazard Class(es):	
Class:	NR
Label(s):	—
Packing Group:	—
Environmental Hazards	Not regulated.
Special precautions for user:	—
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.

TDG

UN Number:	
UN Proper Shipping Name:	NOT DG REGULATED
Transport Hazard Class(es)	
Class:	NR
Label(s):	—
Packing Group:	—
Marine Pollutant:	Not regulated.
Special precautions for user:	—

15. REGULATORY INFORMATION

Canadian Controlled Products Regulations:

This product has been classified according to the hazard criteria of the Canadian Controlled Products Regulations, Section 33, and the MSDS contains all required information.

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

Manganese

Nickel

Reportable quantity

Included in the regulation but with no data values. See regulation for further details.

100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Acute (Immediate)

Chronic (Delayed)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity

Manganese

Nickel

Reportable quantity

Included in the regulation but with no data values. See regulation for further details.

100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity

Iron

Barium fluoride

Iron oxide

Manganese

Aluminum and/or aluminum alloys (as Al)

Lithium fluoride

Magnesium

Nickel

Lithium oxide

Silicon dioxide (amorphous)

Calcium oxide

Zirconium alloys and compounds (as Zr)

Potassium fluorosilicate

Threshold Planning Quantity

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity

Barium fluoride

Manganese

Aluminum and/or aluminum alloys (as Al)

Nickel

Reporting threshold for other users

10000 lbs

10000 lbs

10000 lbs

10000 lbs

Reporting threshold for manufacturing and processing

25000 lbs.

25000 lbs.

25000 lbs.

25000 lbs.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Nickel

Carcinogenic.

WARNING: This product contains or produces a chemical known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code Section 25249.5 et seq.)

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Barium fluoride
Iron oxide
Manganese
Aluminum and/or aluminum alloys (as Al)
Lithium fluoride
Magnesium

US. Massachusetts RTK - Substance List**Chemical Identity**

Nickel

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Barium fluoride
Iron oxide
Manganese
Aluminum and/or aluminum alloys (as Al)
Lithium fluoride
Magnesium
Nickel

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

Inventory Status:

Japan (ENCS) List:	One or more components are not listed or are exempt from listing.
China Inv. Existing Chemical Substances:	One or more components are not listed or are exempt from listing.
Canada NDSL Inventory:	One or more components are not listed or are exempt from listing.
Philippines PICCS:	One or more components are not listed or are exempt from listing.
Japan ISHL Listing:	One or more components are not listed or are exempt from listing.
Japan Pharmacopoeia Listing:	One or more components are not listed or are exempt from listing.
Australia AICS:	One or more components are not listed or are exempt from listing.
Canada DSL Inventory List:	One or more components are not listed or are exempt from listing.
EINECS, ELINCS or NLP:	One or more components are not listed or are exempt from listing.
Korea Existing Chemicals Inv. (KECI):	One or more components are not listed or are exempt from listing.
US TSCA Inventory:	One or more components are not listed or are exempt from listing.
New Zealand Inventory of Chemicals:	One or more components are not listed or are exempt from listing.

16. OTHER INFORMATION**Definitions:**

The Maximum Fume Exposure Guideline™ (MFEG)™ is a guideline limit for total welding fume exposure for a specific consumable product which may be used by employers to manage worker exposure to welding fume where that product is used. The MFEG™ is an estimate of the level of total welding fume exposure for a given product above which the exposure limit for one of the fume constituents may be exceeded. The exposure limits referenced are the American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV®) and the U.S. OSHA Permissible Exposure Limit (PEL) whichever limit is lower. The MFEG™ never exceeds 5 mg/m³ which is the maximum recommended exposure limit for total welding fume. **The MFEG™ is intended to serve as a general guideline to assist in the management of workplace exposure to welding fume and does not replace the regular measurement and analysis of worker exposure to individual welding fume constituents.**

The Maximum Dust Exposure Guideline™ (MDEG)™ is provided to assist with the management of workplace exposures where granular solid welding products or other materials are being utilized. It is derived from relevant compositional data and estimates the lowest level of total airborne dust exposure, for a given product, at which

some specific constituent might potentially exceed its individual exposure limit. The specific exposure limits referenced are the American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV®) and the U. S. OSHA Permissible Exposure Limit (PEL), which ever value is the lowest. The MDEG™ is never greater than 10 mg/m³ as this is the airborne exposure guideline for total particulate (total dust). **The MDEG™ is intended to serve as a general guideline to assist in the management of workplace exposure and does not replace the regular measurement and analysis of worker exposure to individual airborne dust constituents.**

Revision Date: 04/14/2015

Most recent revision(s) are noted by the bold, double bars in the left-hand margin throughout this document.

Further Information: Additional information is available by request.

Disclaimer: The Lincoln Electric Company urges each end user and recipient of this SDS to study it carefully. See also www.lincolnelectric.com/safety. If necessary, consult an industrial hygienist or other expert to understand this information and safeguard the environment and protect workers from potential hazards associated with the handling or use of this product. This information is believed to be accurate as of the revision date shown above. However, no warranty, expressed or implied, is given. Because the conditions or methods of use are beyond Lincoln Electric's control, we assume no liability resulting from the use of this product. Regulatory requirements are subject to change and may differ between various locations. Compliance with all applicable Federal, State, Provincial, and local laws and regulations remain the responsibility of the user.

© 2015 Lincoln Global, Inc. All Rights Reserved.